


## Surface Mount Switching Diodes


### MMBD4148

#### ■ Features

- Fast Switching Speed
- Surface Mount Package Ideally Suited for Automatic Insertion
- For General Purpose Switching Applications
- High Conductance



#### ■ PIN Array



#### ■ Absolute Maximum Ratings Ta = 25°C

Parameter	Symbol	Rating	Unit
Non-Repetitive Peak Reverse Voltage	V <sub>RM</sub>	100	V
Peak Repetitive Reverse Voltage	V <sub>RRM</sub>		
Working Peak Reverse Voltage	V <sub>RWM</sub>	75	V
DC Blocking Voltage	V <sub>R</sub>		
RMS Reverse Voltage	V <sub>R(RMS)</sub>	53	V
Forward Continuous Current (*)	I <sub>FM</sub>	300	mA
Average Rectified Output Current (*)	I <sub>O</sub>	200	mA
Non-Repetitive Peak Forward Surge Current @ t = 1.0 μ s @ t = 1.0s	I <sub>FSM</sub>	2.0 1.0	A
Power Dissipation (*)	P <sub>D</sub>	350	mW
Thermal Resistance Junction to Ambient Air (*)	R <sub>θ JA</sub>	357	°C/W
Operating and Storage Temperature Range	T <sub>j, T<sub>STG</sub></sub>	-65 to +150	°C

\* Device mounted on glass epoxy PCB 1.6" x 1.6" x 0.06"; mounting pad for the cathode lead min. 0.93in<sup>2</sup>.

**MMBD4148**■ Electrical Characteristics  $T_a = 25^\circ\text{C}$ 

Parameter	Symbol	Testconditons	Min	Typ	Max	Unit
Reverse Breakdown Voltage (*)	$V_{(BR)R}$	$I_R = 100 \mu\text{A}$	75			V
Forward Voltage (*)	$V_F$	$I_F = 1.0\text{mA}$		0.715		V
		$I_F = 10\text{mA}$		0.855		
		$I_F = 50\text{mA}$		1.0		
		$I_F = 150\text{mA}$		1.25		
Leakage Current (*)	$I_R$	$V_R = 75\text{V}$		1.0		$\mu\text{A}$
		$V_R = 75\text{V}, T_j = 150^\circ\text{C}$		50		
		$V_R = 25\text{V}, T_j = 150^\circ\text{C}$		30		
		$V_R = 20\text{V}$		25		
Total Capacitance	$C_T$	$V_R = 0, f = 1.0\text{MHz}$		2.0		pF
Reverse Recovery Time	$t_{rr}$	$I_F = I_R = 10\text{mA}, I_{rr} = 0.1 \times I_R, R_L = 100 \Omega$		4.0		ns

\* Short duration test pulse used to minimize self-heating effect.

## ■ Marking

Marking	KA2
---------	-----