


High-Precision Voltage Detector

S-80737AN-D1-X

■ Features

- Ultra-Low Current Consumption 1.0 μ A Typ.(V_{DD} = 4.5V)
- High-Precision Detection Voltage $\pm 2.4\%$
- Wide Operating Voltage Range 1.0 to 15V
- Good Hysteresis Characteristics 5% Typ.
- Wide Operating Temperature Range -30 $^{\circ}$ C to +80 $^{\circ}$ C
- Nch Open-Drain

■ Absolute Maximum Ratings Ta = 25 $^{\circ}$ C

Parameter	Symbol	Rating	Unit
Power Supply Voltage	V _{DD} - V _{SS}	18	V
Input Voltage	V _{IN}	V _{SS} -0.3 to V _{DD} +0.3	
Output Voltage	V _{OUT}	V _{SS} -0.3 to 18	
Output Current	I _{OUT}	50	mA
Power Dissipation	P _D	200	mW
Operating Temperature	T _{opr}	-30 to +80	$^{\circ}$ C
Storage Temperature	T _{stg}	-40 to +125	

Caution: Keep static electricity electricity to a minimum.

■ Electrical Characteristics Ta = 25 $^{\circ}$ C

Parameter	Symbol	Conditions	Min	Typ	Max	Unit	Test Circuit
Detection Voltage	-V _{DET}		3.611	3.700	3.789	V	1
Hysteresis Width	V _{HYS}		-V _{DET} x0.02	-V _{DET} x0.05	-V _{DET} x0.08	V	1
Current Consumption	I _{SS}	V _{DD} = 6.0V	—	1.0	3.0	μ A	2
Operating Voltage	V _{DD}		1.0	—	15.0	V	1
Output Current	I _{OUT}	V _{DS} = 0.5V, V _{DD} = 1.2V	0.23	0.50	—	mA	3
		V _{DS} = 0.5V, V _{DD} = 2.4V	1.60	3.70	—		
Temperature Characteristic of -V _{DET}	$\frac{\Delta -V_{DET}}{\Delta Ta}$	Ta = -30 $^{\circ}$ C to 80 $^{\circ}$ C	—	± 0.46	—	mV/ $^{\circ}$ C	—